NSN 5320-01-088-7452

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-088-7452 **Thread Class:** За **Thread Direction:** Right-hand Fastener Length: Between 0.565 inches and 0.585 inches **Head Style:** Err-090 **Head Height:** Between 0.064 inches and 0.074 inches Width Between Flats: Between 0.0791 inches and 0.0806 inches **Shank Diameter:** Between 0.2177 inches and 0.2182 inches **Shank Style:** Pin-rivet, straight, threaded **Head Major Diameter:** Between 0.370 inches and 0.390 inches Lubrication: Cetyl alcohol, specification 305, hi-shear corp **Grip Length:** 0.255 inches Thready Qty Per Inch (tpi): 32 **Thread Size:** 0.190 inches **Shear Strength:** 125000 single pounds per square inch Material: Steel comp 431 **Material Specification:** Ams 5628 assn standard single material response or mil-s-18732 military specification single material response **Surface Treatment: Passivate Surface Treatment Specification:** 258, fscm 73197 mfr ref single treatment response **Thread Series Designator:** Unjf Shelf Life: N/a

--

Unit Of Measure:

NSN 5320-01-088-7452

Pin-rivet - Page 2 of 2



_		••	• •				
וו	em	ш	112	rız	211	n	٠.

No

Fiig:

A528u0

Mil-std (military Standard):

Mil-s-18732 spec.