## NSN 5320-01-091-1864

Blind Rivet - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5320-01-091-1864

3· · · · · · · · · · · · · · · · · · ·
Fastener Length:
Between 0.541 inches and 0.561 inches
Head Style:
Universal
Head Height:
Between 0.054 inches and 0.064 inches
Shank Diameter:
Between 0.139 inches and 0.143 inches
Shank Style:
Self-plugging mechanically locked stem
Head Major Diameter:
Between 0.240 inches and 0.260 inches
Expansion Device:
Serrated stem-type w
End Application:
Wsd: helicopter, super jolly h-53; aircraft, b-1b; aircraft, hercules c-130; aircraft, harrier av-8b; aircraft, eagle f-15; aircraft, galaxy c-5;
aircraft, ac-130h, mc-130h, ec-130e, hc-130; helicopter, cobra/attack, ah-1j; helicopter observation (ahip), oh-58d
Grip Length:
Between 0.376 inches and 0.437 inches
Criticality Code Justification:
Feat
Special Features:
Ns" letters after the material code "b" indicate no preference to lock type (may be visible or internal). Rivets with no letter code (indicating
visible lock type) and rivets with the letter "h" after the material code (indicating internal lock type) are both acceptable for this item of supply;
weapon system essential see agavgwsd
Material:
Steel comp 8740 stem
Material Specification:
Qq-a-430 federal specification 1st material response sleeve
Surface Treatment:
Cadmium stem
Surface Treatment Specification:
Qq-p-416 type2, class 2 federal specification single treatment response stem
Shelf Life:
N/a
Unit Of Measure:
<del></del>
Demilitarization:
No

Fiig:

A040a0