# NSN 5320-01-091-3528

Blind Rivet - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5320-01-091-3528

# Fastener Length:

Between 0.666 inches and 0.686 inches

#### Head Style:

Flush (flat) countersunk (included angle - less than 135 degrees w or w/o chamfer)

# Shank Diameter:

Between 0.139 inches and 0.143 inches

# Head Major Diameter:

Between 0.221 inches and 0.229 inches

# Expansion Device:

Serrated stem-type w

# Grip Length:

Between 0.501 inches and 0.562 inches

# Countersink Angle:

100.0 degrees

# Special Features:

Ns" letters after the material code "b" indicate no preference to lock type (may be visible or internal). Rivets with no letter code (indicating

visible lock type) and rivets with the letter "h" after the material code (indicating internal lock type) are both acceptable for this item of supply. **Material:** 

Steel comp 8740 stem

#### Material Specification:

Qq-a-430 federal specification 1st material response sleeve

#### Surface Treatment:

Cadmium stem

#### Surface Treatment Specification:

Qq-a-416, type 2, class 2 federal specification single treatment response stem

#### Shelf Life:

N/a

#### Unit Of Measure:

---

#### Demilitarization:

No

Fiig:

A040a0