NSN 5320-01-091-8600

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-091-8600

Thread Class:
3a
Thread Direction:
Right-hand
Fastener Length:
Between 1.121 inches and 1.146 inches
Head Style:
Flush countersunk
Shank Diameter:
0.3403 inches
Shank Style:
Pin-rivet, tapered, threaded
Head Major Diameter:
0.508 inches
Tip Diameter:
0.3280 inches
Lubrication:
Dry film and cetyl alcohol
Grip Length:
Between 0.740 inches and 0.755 inches
Thready Qty Per Inch (tpi):
24
Min. Tensile Strength (psi):
220000 pounds per square inch
Thread Size:
0.312 inches
Shear Strength:
125000 single pounds per square inch
Countersink Angle:
Between 99.0 degrees and 101.0 degrees
Special Features:
8-32unjc-3b thread size, 0.280 in. Length along the longitudinal axis from the head end, 0.120 in. Slot length, 0.060 in. Slot width located
0.220 in. From top of head to center of slot
Material:
Steel comp xm-13
Material Specification:
Ams 5629 assn standard single material response
Surface Treatment:
Passivate
Surface Treatment Specification:
Qq-p-35 federal specification single treatment response

Unjf

Thread Series Designator:

NSN 5320-01-091-8600

Pin-rivet - Page 2 of 2



_					
٠.	n	_	I+	18	e:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A528u0