

View Online at <https://aerobasegroup.com/nsn/5320-01-091-9175>

Fastener Length:

Between 0.193 inches and 0.213 inches

Head Style:

Universal

Head Height:

Between 0.067 inches and 0.077 inches

Shank Diameter:

Between 0.172 inches and 0.176 inches

Head Major Diameter:

Between 0.302 inches and 0.322 inches

Expansion Device:

Serrated stem-type w

End Application:

W/s: aircraft, stratalifter c-135; aircraft, eagle f-15; aircraft, phantom f-4, helicopter, seahawk, h-60; helicopter, electronic countermeasures, eh-60a; aircraft, thunderbolt ii, a-10; aircraft, galaxy c-5; helicopter, super jolly h-53; aircraft, starlifter c-141

Grip Length:

0.062 inches

Special Features:

Ns" letters after the material code "b" indicate no preference to lock type (may be visible or internal). Rivets with no letter code (indicating visible lock type) and rivets with the letter "h" after the material code (indicating internal lock type) are both acceptable for this item of supply.

Material:

Steel comp 8740 stem

Material Specification:

Qq-a-430 federal specification single material response sleeve

Surface Treatment:

Cadmium stem

Surface Treatment Specification:

Qq-p-416 type2, class 2 federal specification single treatment response stem

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A040a0