

View Online at <https://aerobasegroup.com/nsn/5320-01-091-9175>

**Fastener Length:**

Between 0.193 inches and 0.213 inches

**Head Style:**

Universal

**Head Height:**

Between 0.067 inches and 0.077 inches

**Shank Diameter:**

Between 0.172 inches and 0.176 inches

**Head Major Diameter:**

Between 0.302 inches and 0.322 inches

**Expansion Device:**

Serrated stem-type w

**End Application:**

W/s: aircraft, stratalifter c-135; aircraft, eagle f-15; aircraft, phantom f-4, helicopter, seahawk, h-60; helicopter, electronic countermeasures, eh-60a; aircraft, thunderbolt ii, a-10; aircraft, galaxy c-5; helicopter, super jolly h-53; aircraft, starlifter c-141

**Grip Length:**

0.062 inches

**Special Features:**

Ns" letters after the material code "b" indicate no preference to lock type (may be visible or internal). Rivets with no letter code (indicating visible lock type) and rivets with the letter "h" after the material code (indicating internal lock type) are both acceptable for this item of supply.

**Material:**

Steel comp 8740 stem

**Material Specification:**

Qq-a-430 federal specification single material response sleeve

**Surface Treatment:**

Cadmium stem

**Surface Treatment Specification:**

Qq-p-416 type2, class 2 federal specification single treatment response stem

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A040a0