

View Online at <https://aerobasegroup.com/nsn/5320-01-092-1064>

**Fastener Length:**

0.586 inches

**Head Style:**

Flush (flat) countersunk (included angle - less than 135 degrees w or w/o chamfer)

**Shank Diameter:**

Between 0.155 inches and 0.159 inches

**Shank Style:**

Self-plugging mechanically locked stem

**Head Major Diameter:**

0.290 inches

**Expansion Device:**

Serrated stem-type w

**Lubrication:**

Dry film

**Grip Length:**

Between 0.376 inches and 0.437 inches

**Countersink Angle:**

Between 99.0 degrees and 101.0 degrees

**Special Features:**

May be slosch cleaned with mil-c-38736 cleaner before installation

**Material:**

Aluminum alloy 5056 sleeve

**Material Specification:**

Qq-a-430 federal specification single material response stem

**Surface Treatment:**

Anodize stem or chromate stem

**Surface Treatment Specification:**

Mil-a-8625 military specification 1st treatment response stem or mil-c-5541 military specification 2nd treatment response stem

**Specification Data:**

80205-nas1921 professional/industrial association standard

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A040a0

**Mil-std (military Standard):**

Mil-a-8625 spec.