# NSN 5320-01-092-5044

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-092-5044

# Thread Class:

3a

**Thread Direction:** 

**Right-hand** 

# Fastener Length:

Between 0.565 inches and 0.585 inches

# Head Style:

Flush countersunk

#### Width Between Flats:

Between 0.0791 inches and 0.0806 inches

# Shank Diameter:

Between 0.1890 inches and 0.1895 inches

#### Shank Style:

#### Head Major Diameter:

0.3016 inches

#### Lubrication:

Cetyl alcohol, specification 305, hi-shear corp

# Grip Length:

0.255 inches

Thready Qty Per Inch (tpi):

32

# Thread Size:

0.190 inches

# Shear Strength:

95000 single pounds per square inch

#### **Countersink Angle:**

100.0 degrees

# Material:

Iron alloy 660

#### **Material Specification:**

Ams 5731 assn standard single material response or ams 5737 assn standard single material response

#### Surface Treatment:

Passivate

#### Surface Treatment Specification:

258, fscm 73197 mfr ref single treatment response

#### **Thread Series Designator:**

Unjf

# Shelf Life:

N/a

# Unit Of Measure:

--

# NSN 5320-01-092-5044

Pin-rivet - Page 2 of 2

Demilitarization:

No

Fiig:

A528u0

