NSN 5320-01-092-6985

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-092-6985 **Thread Class:** За **Thread Direction:** Right-hand Fastener Length: Between 1.065 inches and 1.085 inches **Head Style:** Flush countersunk Width Between Flats: Between 0.0791 inches and 0.0806 inches **Shank Diameter:** Between 0.1885 inches and 0.1895 inches **Shank Style:** Pin-rivet, straight, threaded **Head Major Diameter:** 0.356 inches Lubrication: Cetyl alcohol and dry film **End Application:** W/s: aircraft, f-16 **Grip Length:** Between 0.689 inches and 0.750 inches Thready Qty Per Inch (tpi): 32 **Thread Size:** 0.190 inches **Shear Strength:** 108000 single pounds per square inch **Countersink Angle:** Between 99.0 degrees and 101.0 degrees Material: Steel comp 8740 **Material Specification:** Aisi assn standard single material response **Surface Treatment:** Cadmium and chromate **Surface Treatment Specification:** Qq-p-416, type 2, class 2 federal specification single treatment response **Thread Series Designator:** Unjf Shelf Life:

N/a

NSN 5320-01-092-6985

Pin-rivet - Page 2 of 2



	1	:.	~	84				
ι	JN	IT	UΤ	IVI	ea	Sι	ire:	•

--

Demilitarization:

No

Fiig:

A528u0