## NSN 5320-01-093-0786

Pin-rivet - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5320-01-093-0786



## **Thread Class:**

3a

**Thread Direction:** 

**Right-hand** 

## Fastener Length:

Between 0.996 inches and 1.021 inches

## Head Style:

Err-090

#### Head Height:

Between 0.068 inches and 0.080 inches

#### Shank Diameter:

0.3417 inches

#### Shank Style:

Pin-rivet, tapered, threaded

#### Head Major Diameter:

Between 0.490 inches and 0.502 inches

#### Tip Diameter:

0.3306 inches

## Lubrication:

Cetyl alcohol and dry film

#### Grip Length:

Between 0.615 inches and 0.630 inches

## Thready Qty Per Inch (tpi):

24

#### Min. Tensile Strength (psi):

220000 pounds per square inch

#### Thread Size:

0.312 inches

#### Shear Strength:

125000 single pounds per square inch

#### Material:

Steel comp xm-13

#### **Material Specification:**

Ams 5629 assn standard single material response

#### Surface Treatment:

Passivate

## Surface Treatment Specification:

Qq-p-35 federal specification single treatment response

## **Thread Series Designator:**

Unjf

## Shelf Life:

N/a

# NSN 5320-01-093-0786

Pin-rivet - Page 2 of 2

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A528u0

