## NSN 5320-01-093-3161

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-093-3161

Thread Class:
3a
Thread Direction:
Right-hand
Fastener Length:
Between 1.583 inches and 1.608 inches
Head Style:
Err-090
Head Height:
Between 0.082 inches and 0.094 inches
Shank Diameter:
0.4068 inches
Head Major Diameter:
Between 0.582 inches and 0.596 inches
Tip Diameter:
0.3841 inches
Lubrication:
Cetyl alcohol
Grip Length:
Between 1.177 inches and 1.192 inches
Thready Qty Per Inch (tpi):
24
Min. Tensile Strength (psi):
180000 pounds per square inch
Thread Size:
0.375 inches
Shear Strength:
108000 single pounds per square inch
Material:
Steel comp 8740 or steel comp e4340
Material Specification:
Mil-s-6049 military specification 1st material response or mil-s-5000 military specification 2nd material response
Surface Treatment:
Cadmium and chromate
Surface Treatment Specification:
Qq-p-416, type 2, class 2 federal specification single treatment response
Thread Series Designator:
Unjf
Specification Data:
80205-nas1728 professional/industrial association standard
Shelf Life:

N/a

## NSN 5320-01-093-3161

Pin-rivet - Page 2 of 2



	ι	Jn	it	Of	Measure:
--	---	----	----	----	----------

--

Demilitarization:

No

Fiig:

A528u0

Mil-std (military Standard):

Mil-s-6049 spec.