

View Online at <https://aerobasegroup.com/nsn/5320-01-093-5208>

Fastener Length:

Between 0.347 inches and 0.377 inches

Head Style:

Flush (flat) countersunk (included angle - less than 135 degrees w or w/o chamfer)

Shank Diameter:

Between 0.155 inches and 0.159 inches

Shank Style:

Pull through hollow shank

Head Major Diameter:

0.322 inches

Expansion Device:

Plain stem-type t

Grip Length:

Between 0.040 inches and 0.125 inches

Countersink Angle:

Between 120.0 degrees and 124.0 degrees

Material:

Steel comp 1012 mandrel or steel comp 1013 mandrel or steel comp 1015 mandrel or steel comp 1016 mandrel or steel comp 1017 mandrel or steel comp 1018 mandrel or steel comp 1019 mandrel or steel comp 1020 mandrel or steel comp 1021 mandrel or steel comp 1022 mandrel or steel comp 1023 mandrel or steel comp 1524 mandrel or steel comp 1025 mandrel or steel comp 1045 mandrel or steel comp 1046 mandrel or steel comp 1548 mandrel or steel comp 1049 mandrel or steel comp 1050 mandrel or steel comp 1551 mandrel or steel comp 1552 mandrel or steel comp 1053 mandrel or steel comp 1055 mandrel or steel comp 1059 mandrel or steel comp 1060 mandrel or steel comp 1561 mandrel or steel comp 1064 mandrel or steel comp 1065 mandrel or steel comp 1566 mandrel or steel comp 1069 mandrel or steel comp 1070 mandrel or steel comp 1572 mandrel or steel comp 1074 mandrel or steel comp 1075 mandrel

Material Specification:

Qq-a-430 federal specification single material response body

Surface Treatment:

Phosphate zinc mandrel or cadmium mandrel or cadmium mandrel and chromate mandrel or cadmium mandrel and phosphate mandrel or zinc mandrel and chromate mandrel

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A040a0