NSN 5320-01-093-7054

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-093-7054 **Thread Class:** За **Thread Direction:** Right-hand Fastener Length: Between 1.510 inches and 1.535 inches **Head Style:** Flush countersunk **Shank Diameter:** 0.2884 inches **Shank Style:** Pin-rivet, tapered, threaded **Head Major Diameter:** 0.439 inches Tip Diameter: 0.2668 inches Lubrication: Dry film and cetyl alcohol **Grip Length:** Between 1.177 inches and 1.192 inches Thready Qty Per Inch (tpi): 28 Min. Tensile Strength (psi): 220000 pounds per square inch **Thread Size:** 0.250 inches **Shear Strength:** 125000 single pounds per square inch **Countersink Angle:** Between 99.0 degrees and 101.0 degrees Material: Steel comp xm-13 **Material Specification:** Ams 5629 assn standard single material response **Surface Treatment: Passivate Surface Treatment Specification:** Qq-p-35 federal specification single treatment response **Thread Series Designator:**

Unjf

Shelf Life:

N/a

NSN 5320-01-093-7054

Pin-rivet - Page 2 of 2



	Of			

--

Demilitarization:

No

Fiig:

A528u0