# NSN 5320-01-093-7275

Pin-rivet - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5320-01-093-7275



#### **Thread Class:**

3a

**Thread Direction:** 

**Right-hand** 

#### Fastener Length:

Between 1.447 inches and 1.472 inches

#### Head Style:

Flush countersunk

#### Shank Diameter:

0.275 inches

#### Shank Style:

Pin-rivet, tapered, threaded

#### Head Major Diameter:

0.426 inches

#### Tip Diameter:

0.2551 inches

## Lubrication:

Cetyl alcohol and dry film

#### Grip Length:

Between 1.115 inches and 1.130 inches

#### Thready Qty Per Inch (tpi):

28

#### Min. Tensile Strength (psi):

220000 pounds per square inch

#### **Thread Size:**

0.250 inches

#### Shear Strength:

125000 single pounds per square inch

#### **Countersink Angle:**

Between 99.0 degrees and 101.0 degrees

#### Material:

Steel comp xm-13

#### **Material Specification:**

Ams 5629 assn standard single material response

#### Surface Treatment:

Passivate

#### Surface Treatment Specification:

Qq-p-35 federal specification single treatment response

## **Thread Series Designator:**

Unjf

#### Shelf Life:

N/a

# NSN 5320-01-093-7275

Pin-rivet - Page 2 of 2

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A528u0

