NSN 5320-01-094-0876

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-094-0876 **Thread Class:** За **Thread Direction:** Right-hand Fastener Length: Between 1.771 inches and 1.796 inches **Head Style:** Err-090 **Head Height:** Between 0.068 inches and 0.080 inches **Shank Diameter:** 0.3703 inches **Shank Style:** Pin-rivet, tapered, threaded **Head Major Diameter:** Between 0.533 inches and 0.544 inches Tip Diameter: 0.3436 inches Lubrication: Cetyl alcohol **Grip Length:** Between 1.365 inches and 1.380 inches Thready Qty Per Inch (tpi): 24 Min. Tensile Strength (psi): 180000 pounds per square inch **Thread Size:** 0.312 inches **Shear Strength:** 108000 single pounds per square inch Material: Steel comp 8740 or steel comp e4340 **Material Specification:** Mil-s-6049 military specification 1st material response or mil-s-5000 military specification 2nd material response **Surface Treatment:** Cadmium and chromate **Surface Treatment Specification:** Qq-p-416, type 2, class 2 federal specification single treatment response

Unjf

Shelf Life:

Thread Series Designator:

N/a

NSN 5320-01-094-0876

Pin-rivet - Page 2 of 2



	ι	Jn	it	Of	Measure:
--	---	----	----	----	----------

--

Demilitarization:

No

Fiig:

A528u0

Mil-std (military Standard):

Mil-s-6049 spec.