NSN 5320-01-094-2233

Blind Rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-094-2233 **Thread Class:** 3b **Thread Direction:** Right-hand **Head Style:** Flush (flat) countersunk (included angle - less than 135 degrees w or w/o chamfer) **Shank Diameter:** Between 0.255 inches and 0.257 inches **Shank Style:** Blind rivet, nut and bolt (assembly) **Head Major Diameter:** 0.317 inches **Expansion Device:** Threaded mandrel **Grip Length:** 0.062 inches Thready Qty Per Inch (tpi): 32 **Thread Size:** 0.164 inches **Shear Strength:** 125000 single pounds per square inch **Countersink Angle:** Between 98.0 degrees and 102.0 degrees **Special Features:** Furnished without bolt **Heat Treatment:** Annealed sleeve Material: Steel comp 431 expander **Surface Treatment:** Cadmium expander **Surface Treatment Specification:** Qq-p-416, type 1, class 2 federal specification single treatment response expander **Thread Series Designator:** Unc Shelf Life: N/a **Unit Of Measure:**

Demilitarization: No

NSN 5320-01-094-2233

Blind Rivet - Page 2 of 2



Fiig:

A040a0