NSN 5320-01-094-2249

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-094-2249 **Thread Class:** За **Thread Direction:** Right-hand Fastener Length: Between 1.572 inches and 1.597 inches **Head Style:** Flush countersunk **Shank Diameter:** 0.2884 inches **Head Major Diameter:** 0.439 inches Tip Diameter: 0.2655 inches Lubrication: Dry film and cetyl alcohol **Grip Length:** Between 1.240 inches and 1.255 inches Thready Qty Per Inch (tpi): 28 Min. Tensile Strength (psi): 220000 pounds per square inch **Thread Size:** 0.250 inches **Shear Strength:** 125000 single pounds per square inch **Countersink Angle:** Between 99.0 degrees and 101.0 degrees Material: Steel comp xm-13 **Material Specification:** Ams 5629 assn standard single material response **Surface Treatment: Passivate Surface Treatment Specification:** Qq-p-35 federal specification single treatment response **Thread Series Designator:** Unjf Shelf Life:

Unit Of Measure:

N/a

NSN 5320-01-094-2249

Pin-rivet - Page 2 of 2



_						
11	em)	 tor	172	+ 1	nn	

No

Fiig:

A528u0