

View Online at <https://aerobasegroup.com/nsn/5320-01-094-7410>

Thread Class:

3a

Thread Direction:

Right-hand

Fastener Length:

Between 1.073 inches and 1.093 inches

Head Style:

Flush countersunk

Width Between Flats:

Between 0.0947 inches and 0.0967 inches

Shank Diameter:

Between 0.2490 inches and 0.2495 inches

Shank Style:

Pin-riquet, straight, threaded

Head Major Diameter:

0.5066 inches

Lubrication:

Cetyl alcohol, specification 305, hi-shear corp

End Application:

Aircraft, b-2 bomber (atb), f/a-18e/f hornet aircraft

Grip Length:

Between 0.683 inches and 0.693 inches

Thread Qty Per Inch (tpi):

28

Min. Tensile Strength (psi):

160000 pounds per square inch

Thread Size:

0.250 inches

Shear Strength:

95000 single pounds per square inch

Countersink Angle:

100.0 degrees

Material:

Iron alloy 660

Material Specification:

Ams 5737 assn standard single material response or ams 5731 assn standard single material response

Surface Treatment:

Passivate

Surface Treatment Specification:

258, fscm 73197 mfr ref single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A528u0