# NSN 5320-01-094-9945

Pin-rivet - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5320-01-094-9945



#### **Thread Class:**

3a

**Thread Direction:** 

**Right-hand** 

#### Fastener Length:

Between 0.910 inches and 0.950 inches

#### Head Style:

Err-090

#### Head Height:

Between 0.079 inches and 0.086 inches

#### Width Between Flats:

Between 0.0791 inches and 0.0806 inches

#### Shank Diameter:

Between 0.2010 inches and 0.2025 inches

#### Shank Style:

Pin-rivet, straight, threaded

#### Head Major Diameter:

Between 0.298 inches and 0.312 inches

#### Grip Length:

Between 0.563 inches and 0.625 inches

## Thready Qty Per Inch (tpi):

32

#### Thread Size:

0.190 inches

#### Shear Strength:

108000 single pounds per square inch

#### **Special Features:**

Color gold

#### Material:

Steel comp 8740

#### **Material Specification:**

Aisi assn standard single material response

#### Surface Treatment:

Cadmium and chromate

#### Surface Treatment Specification:

Qq-p-416, type 2, class 2 federal specification single treatment response

### **Thread Series Designator:**

Unjf

# Shelf Life:

N/a

## Unit Of Measure:

--

# NSN 5320-01-094-9945

Pin-rivet - Page 2 of 2

Demilitarization:

No

Fiig:

A528u0

