## NSN 5320-01-095-5772



Pin-rivet - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5320-01-095-5772 **Thread Class:** За **Thread Direction:** Right-hand Fastener Length: Between 1.036 inches and 1.076 inches **Head Style:** Err-090 **Head Height:** Between 0.070 inches and 0.078 inches Width Between Flats: Between 0.1270 inches and 0.1295 inches **Shank Diameter:** Between 0.311 inches and 0.312 inches **Shank Style:** Pin-rivet, straight, threaded **Head Major Diameter:** Between 0.483 inches and 0.503 inches Lubrication: Dry film **Grip Length:** Between 0.563 inches and 0.625 inches Thready Qty Per Inch (tpi): 24 **Thread Size:** 0.312 inches **Shear Strength:** 156000 single pounds per square inch Material: Steel comp h11 **Material Specification:** Ams 6485 assn standard single material response or ams 6487 assn standard single material response **Surface Treatment:** Nickel and cadmium **Surface Treatment Specification:** Ams 2416 assn standard single treatment response

**Thread Series Designator:** 

Unjf

**Specification Data:** 

80205-nas4450 professional/industrial association standard

Shelf Life:

N/a

## NSN 5320-01-095-5772

Pin-rivet - Page 2 of 2



	1	:.	~	84				
ι	JN	IT	UΤ	IVI	ea	Sι	ire:	•

--

Demilitarization:

No

Fiig:

A528u0