# NSN 5320-01-095-5773

Pin-rivet - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5320-01-095-5773



#### **Thread Class:**

3a

**Thread Direction:** 

**Right-hand** 

# Fastener Length:

Between 1.099 inches and 1.139 inches

#### Head Style:

Err-090

#### Head Height:

Between 0.070 inches and 0.078 inches

# Width Between Flats:

Between 0.1270 inches and 0.1295 inches

#### Shank Diameter:

Between 0.311 inches and 0.312 inches

#### Shank Style:

Pin-rivet, straight, threaded

#### Head Major Diameter:

Between 0.483 inches and 0.503 inches

#### Lubrication:

Dry film

## Grip Length:

Between 0.626 inches and 0.688 inches

# Thready Qty Per Inch (tpi):

24

#### Thread Size:

0.312 inches

#### Shear Strength:

156000 single pounds per square inch

#### Material:

Steel comp h11

#### **Material Specification:**

Ams 6485 assn standard single material response or ams 6487 assn standard single material response

#### Surface Treatment:

Nickel and cadmium

#### Surface Treatment Specification:

Ams 2416 assn standard single treatment response

#### **Thread Series Designator:**

Unjf

## **Specification Data:**

80205-nas4450 professional/industrial association standard

# Shelf Life:

N/a

# NSN 5320-01-095-5773

Pin-rivet - Page 2 of 2

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A528u0

