
# NSN 5320-01-095-5774

Pin-rivet - Page 1 of 2



### **Thread Class:**

3a

**Thread Direction:** 

**Right-hand** 

## Fastener Length:

Between 1.161 inches and 1.201 inches

#### Head Style:

Err-090

#### Head Height:

Between 0.070 inches and 0.078 inches

# Width Between Flats:

Between 0.1270 inches and 0.1295 inches

### Shank Diameter:

Between 0.311 inches and 0.312 inches

#### Shank Style:

Pin-rivet, straight, threaded

#### Head Major Diameter:

Between 0.483 inches and 0.503 inches

#### Lubrication:

Dry film

## Grip Length:

Between 0.689 inches and 0.750 inches

## Thready Qty Per Inch (tpi):

24

### Thread Size:

0.312 inches

### Shear Strength:

156000 single pounds per square inch

### Material:

Steel comp h11

### **Material Specification:**

Ams 6485 assn standard single material response or ams 6487 assn standard single material response

#### Surface Treatment:

Nickel and cadmium

### Surface Treatment Specification:

Ams 2416 assn standard single treatment response

## **Thread Series Designator:**

Unjf

# **Specification Data:**

80205-nas4450 professional/industrial association standard

# Shelf Life:

N/a



# NSN 5320-01-095-5774

Pin-rivet - Page 2 of 2

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A528u0

