# NSN 5320-01-097-4284

Blind Rivet - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5320-01-097-4284

# Fastener Length:

0.303 inches

### Head Style:

Undercut pan no. 2

# Head Height:

Between 0.125 inches and 0.135 inches

## Shank Diameter:

Between 0.213 inches and 0.215 inches

#### Shank Style:

Self-plugging mechanically locked stem

#### Head Major Diameter:

Between 0.305 inches and 0.332 inches

#### **Expansion Device:**

Serrated stem-type w

#### Grip Length:

Between 0.094 inches and 0.157 inches

## Shear Strength:

3450 single pounds per square inch

#### Material:

Steel comp 8740 stem

#### **Material Specification:**

Ams 5737 assn standard single material response mechanical lock

### Surface Treatment:

Cadmium

## Surface Treatment Specification:

Mil-f-81177 military specification single treatment response

#### Supplementary Features:

Stem cadmium coat unbrightened cyanide

#### **Specification Data:**

81755-c9503 manufacturers specification control and 29666-osbp-t manufacturers standard

#### Shelf Life:

N/a

## Unit Of Measure:

```
---
```

#### Demilitarization:

No

Fiig:

A040a0

## Mil-std (military Standard):

Mil-f-81177 spec.