

View Online at <https://aerobasegroup.com/nsn/5320-01-097-8088>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Fastener Length:**

Between 0.849 inches and 0.889 inches

**Head Style:**

Flush countersunk

**Width Between Flats:**

Between 0.1270 inches and 0.1295 inches

**Shank Diameter:**

Between 0.3110 inches and 0.3120 inches

**Shank Style:**

Pin-riquet, straight, threaded

**Head Major Diameter:**

0.492 inches

**Lubrication:**

Dry film

**Grip Length:**

Between 0.376 inches and 0.438 inches

**Thready Qty Per Inch (tpi):**

24

**Thread Size:**

0.312 inches

**Shear Strength:**

156000 single pounds per square inch

**Countersink Angle:**

Between 99.0 degrees and 101.0 degrees

**Material:**

Steel comp h11

**Material Specification:**

Ams 6485 assn standard single material response or ams 6487 assn standard single material response

**Surface Treatment:**

Nickel and cadmium

**Surface Treatment Specification:**

Ams 2416 assn standard single treatment response

**Thread Series Designator:**

Unjf

**Specification Data:**

80205-nas4452 professional/industrial association standard

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A528u0