NSN 5320-01-098-1599

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-098-1599 **Thread Class:** За **Thread Direction:** Right-hand Fastener Length: Between 1.572 inches and 1.597 inches **Head Style:** Err-090 **Head Height:** Between 0.058 inches and 0.070 inches **Shank Diameter:** 0.2896 inches **Shank Style:** Pin-rivet, tapered, threaded **Head Major Diameter:** Between 0.411 inches and 0.421 inches Tip Diameter: 0.2655 inches Lubrication: Cetyl alcohol **End Application:** W/s: aircraft, starlifter c-141 **Grip Length:** Between 1.240 inches and 1.255 inches Thready Qty Per Inch (tpi): 28 Min. Tensile Strength (psi): 180000 pounds per square inch **Thread Size:** 0.250 inches Material: Steel comp e4340 or steel comp 8740 **Material Specification:** Mil-s-5000 military specification 1st material response or mil-s-6049 military specification 2nd material response **Surface Treatment:**

Cadmium and chromate **Surface Treatment Specification:** Qq-p-416, type 2, class 2 federal specification single treatment response **Thread Series Designator:** Unjf Shelf Life: N/a

NSN 5320-01-098-1599

Pin-rivet - Page 2 of 2



U	n	it	Of	Μe	eas	ur	e:

--

Demilitarization:

No

Fiig:

A528u0

Mil-std (military Standard):

Mil-s-5000 spec.