NSN 5320-01-098-6278



Pin-rivet - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5320-01-098-6278 **Thread Class:** За **Thread Direction:** Right-hand Fastener Length: Between 1.396 inches and 1.421 inches **Head Style:** Err-090 **Head Height:** Between 0.068 inches and 0.080 inches **Shank Diameter:** 0.3846 inches **Shank Style:** Pin-rivet, tapered, threaded **Head Major Diameter:** Between 0.548 inches and 0.560 inches Tip Diameter: 0.3658 inches

Lubrication:

Cetyl alcohol **Grip Length:**

Between 0.990 inches and 1.005 inches

Thready Qty Per Inch (tpi):

24

Thread Size:

0.312 inches

Shear Strength:

108000 single pounds per square inch

Material:

Steel comp 8740 or steel comp e4340

Material Specification:

Mil-s-6049 military specification 1st material response or mil-s-5000 military specification 2nd material response

Surface Treatment:

Cadmium and chromate

Surface Treatment Specification:

Qq-p-416, type 2, class 2 federal specification single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

NSN 5320-01-098-6278

Pin-rivet - Page 2 of 2



| Demi | | | |
|------|--|--|--|
| | | | |
| | | | |

No

Fiig:

A528u0

Mil-std (military Standard):

Mil-s-6049 spec.