NSN 5320-01-098-7271

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-098-7271 **Thread Class:** За **Thread Direction:** Right-hand Fastener Length: Between 2.058 inches and 2.083 inches **Head Style:** Err-090 **Head Height:** Between 0.068 inches and 0.080 inches **Shank Diameter:** 0.356 inches **Head Major Diameter:** Between 0.512 inches and 0.524 inches **Tip Diameter:** 0.3228 inches Lubrication: Cetyl alcohol **Grip Length:** Between 1.677 inches and 1.692 inches Thready Qty Per Inch (tpi): 24 Min. Tensile Strength (psi): 180000 pounds per square inch **Thread Size:** 0.312 inches **Shear Strength:** 108000 single pounds per square inch Material: Steel comp e4340 or steel comp 8740 **Material Specification:** Mil-s-5000 military specification 1st material response or mil-s-6049 military specification 2nd material response **Surface Treatment:** Cadmium and chromate **Surface Treatment Specification:** Qq-p-416, type 2, class 2 federal specification single treatment response **Thread Series Designator:** Unjf Shelf Life:

N/a

Unit Of Measure:

NSN 5320-01-098-7271

Pin-rivet - Page 2 of 2



Demi			

No

Fiig:

A528u0

Mil-std (military Standard):

Mil-s-5000 spec.