

View Online at <https://aerobasegroup.com/nsn/5320-01-099-1005>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Fastener Length:**

Between 1.021 inches and 1.046 inches

**Head Style:**

Flush countersunk

**Shank Diameter:**

0.352 inches

**Shank Style:**

Pin-riquet, tapered, threaded

**Head Major Diameter:**

0.522 inches

**Tip Diameter:**

0.3422 inches

**Lubrication:**

Cetyl alcohol

**Grip Length:**

Between 0.615 inches and 0.630 inches

**Thready Qty Per Inch (tpi):**

24

**Thread Size:**

0.312 inches

**Shear Strength:**

108000 single pounds per square inch

**Countersink Angle:**

Between 99.0 degrees and 101.0 degrees

**Material:**

Steel comp 8740 or steel comp e4340

**Material Specification:**

II-s-6049 military specification 10th material response or mil-s-5000 military specification 2nd material response

**Surface Treatment:**

Cadmium and chromate

**Surface Treatment Specification:**

Qq-p-416, type 2, class 2 federal specification single treatment response

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A528u0

**Mil-std (military Standard):**

Mil-s-5000 spec.