NSN 5320-01-099-4720

Pin-rivet - Page 1 of 2

Thread Class:

View Online at https://aerobasegroup.com/nsn/5320-01-099-4720

AeroBase Group

3a **Thread Direction: Right-hand Identification Code Color:** Bronze **Fastener Length:** Between 1.490 inches and 1.510 inches **Head Style:** Err-090 **Head Height:** Between 0.037 inches and 0.047 inches Width Between Flats: Between 0.0791 inches and 0.0801 inches Shank Diameter: Between 0.1625 inches and 0.1635 inches Shank Style: Pin-rivet, straight, threaded Head Major Diameter: Between 0.242 inches and 0.262 inches Lubrication: Cetyl alcohol, specification 305, hi-shear corp Grip Length: Between 1.183 inches and 1.193 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 160000 pounds per square inch Thread Size: 0.164 inches Shear Strength: 95000 single pounds per square inch **Special Features:** Color bronze Material: Steel comp e4340 or steel comp 4140 or steel comp 8740 **Material Specification:** Mil-s-5000 military specification 1st material response or mil-s-5626 military specification 2nd material response or mil-s-6049 military specification 3rd material response Surface Treatment:

Cadmium and chromate

Surface Treatment Specification:

Qq-p-416, type 2, class 2 federal specification single treatment response

NSN 5320-01-099-4720

Pin-rivet - Page 2 of 2

Thread Series Designator:

Unjc

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A528u0

Mil-std (military Standard):

Mil-s-5000 spec.

