## NSN 5320-01-101-3429

Blind Rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-101-3429

Thread Class:
3a
Thread Direction:
Left-hand
Head Style:
Flush (flat) countersunk (included angle - less than 135 degrees w or w/o chamfer)
Shank Diameter:
0.2001 inches
Shank Style:
Threaded self-plugging shank w/sleeve
Head Major Diameter:
0.317 inches
Expansion Device:
Threaded stem
Lubrication:
Dry film and cetyl alcohol
Grip Length:
Between 0.251 inches and 0.313 inches
Thready Qty Per Inch (tpi):
40
Thread Size:
0.138 inches
Countersink Angle:
Between 99.0 degrees and 101.0 degrees
Special Features:
0.1964 in. Second shank diameter
Material:
Iron alloy 660
Material Specification:
Ams 5732 assn standard single material response or ams 5737 assn standard single material response
Surface Treatment:
Passivate
Surface Treatment Specification:
Qq-p-35 federal specification single treatment response
Thread Series Designator:
Unf
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

## NSN 5320-01-101-3429

Blind Rivet - Page 2 of 2



Fiig:

A040a0