
# NSN 5320-01-101-4867

Pin-rivet - Page 1 of 2





### **Thread Class:**

3a

**Thread Direction:** 

**Right-hand** 

## Fastener Length:

Between 1.271 inches and 1.296 inches

### Head Style:

Err-090

#### Head Height:

Between 0.068 inches and 0.080 inches

#### Shank Diameter:

0.3846 inches

#### Head Major Diameter:

Between 0.548 inches and 0.560 inches

#### **Tip Diameter:**

## 0.3684 inches

Lubrication:

Cetyl alcohol

# Grip Length:

Between 0.865 inches and 0.880 inches

## Thready Qty Per Inch (tpi):

24

# Min. Tensile Strength (psi):

180000 pounds per square inch

## Thread Size:

0.312 inches

### Shear Strength:

108000 single pounds per square inch

### Material:

Steel comp 8740 or steel comp e4340

### Material Specification:

Mil-s-6049 military specification 1st material response or mil-s-5000 military specification 2nd material response

#### Surface Treatment:

Cadmium and chromate

### Surface Treatment Specification:

Qq-p-416, type 2, class 2 federal specification single treatment response

# Thread Series Designator:

Unjf

## Shelf Life:

N/a

#### Unit Of Measure:

--

# NSN 5320-01-101-4867

Pin-rivet - Page 2 of 2

Demilitarization:

No

Fiig:

A528u0

Mil-std (military Standard):

Mil-s-6049 spec.

