# NSN 5320-01-101-4872

Pin-rivet - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5320-01-101-4872



# Thread Class:

3a

**Thread Direction:** 

**Right-hand** 

## Fastener Length:

Between 1.098 inches and 1.118 inches

#### Head Style:

Flush countersunk

#### Width Between Flats:

Between 0.1582 inches and 0.1617 inches

#### Shank Diameter:

Between 0.3735 inches and 0.3745 inches

#### Shank Style:

Pin-rivet, straight, threaded

#### Head Major Diameter:

0.695 inches

#### Lubrication:

Dry film and cetyl alcohol

#### Grip Length:

Between 0.501 inches and 0.562 inches

## Thready Qty Per Inch (tpi):

24

#### Thread Size:

0.375 inches

#### Shear Strength:

108000 single pounds per square inch

#### **Countersink Angle:**

Between 99.0 degrees and 101.0 degrees

#### Material:

Steel comp 8740

#### **Material Specification:**

Aisi assn standard single material response

#### Surface Treatment:

Cadmium and chromate

#### Surface Treatment Specification:

Qq-p-416, type 2, class 2 federal specification single treatment response

# **Thread Series Designator:**

Unjf

# Shelf Life:

N/a

## Unit Of Measure:

--

# NSN 5320-01-101-4872

Pin-rivet - Page 2 of 2

Demilitarization:

No

Fiig:

A528u0

