NSN 5320-01-101-6111

Pin-rivet - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5320-01-101-6111

Thread Class:

3a

Thread Direction:

Right-hand

Fastener Length:

Between 0.948 inches and 0.968 inches

Head Style:

Flush countersunk

Width Between Flats:

Between 0.0947 inches and 0.0967 inches

Shank Diameter:

Between 0.2485 inches and 0.2495 inches

Shank Style:

Head Major Diameter:

0.478 inches

Lubrication:

Dry film and cetyl alcohol

Grip Length:

Between 0.501 inches and 0.562 inches

Thready Qty Per Inch (tpi):

28

Thread Size:

0.250 inches

Shear Strength:

108000 single pounds per square inch

Countersink Angle:

Between 99.0 degrees and 101.0 degrees

Material:

Steel comp 8740

Material Specification:

Aisi assn standard single material response

Surface Treatment:

Cadmium and chromate

Surface Treatment Specification:

Qq-p-416, type 2, class 2 federal specification single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:



NSN 5320-01-101-6111

Pin-rivet - Page 2 of 2

Demilitarization:

No

Fiig:

A528u0

