NSN 5320-01-101-6112

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-101-6112 **Thread Class:** За **Thread Direction:** Right-hand Fastener Length: Between 0.928 inches and 0.948 inches **Head Style:** Flush countersunk Width Between Flats: Between 0.1270 inches and 0.1295 inches **Shank Diameter:** Between 0.311 inches and 0.312 inches **Shank Style:** Pin-rivet, straight, threaded **Head Major Diameter:** 0.565 inches Lubrication: Dry film and cetyl alcohol **Grip Length:** Between 0.376 inches and 0.438 inches Thready Qty Per Inch (tpi): 24 **Thread Size:** 0.312 inches **Shear Strength:** 108000 single pounds per square inch **Countersink Angle:** Between 99.0 degrees and 101.0 degrees Material: Steel comp 8740 **Material Specification:** Aisi assn standard single material response **Surface Treatment:** Cadmium and chromate **Surface Treatment Specification:** Qq-p-416, type 2, class 2 federal specification single treatment response **Thread Series Designator:** Unjf Shelf Life: N/a

--

Unit Of Measure:

NSN 5320-01-101-6112

Pin-rivet - Page 2 of 2



Demi			

No

Fiig:

A528u0