NSN 5320-01-102-0369

Pin-rivet - Page 1 of 2

Thread Class:

Right-hand

Head Style:

Thread Direction:

Fastener Length:

Flush countersunk

Between 0.885 inches and 0.905 inches

За



View Online at https://aerobasegroup.com/nsn/5320-01-102-0369

Width Between Flats:
Between 0.0947 inches and 0.0967 inches
Shank Diameter:
Between 0.2485 inches and 0.2495 inches
Shank Style:
Pin-rivet, straight, threaded
Head Major Diameter:
0.478 inches
Lubrication:
Dry film and cetyl alcohol
End Application:
Wsd: aircraft, f-16; aircraft, galaxy c-5
Grip Length:
Between 0.439 inches and 0.500 inches
Thready Qty Per Inch (tpi):
28
Thread Size:
0.250 inches
Shear Strength:
108000 single pounds per square inch
Countersink Angle:
Between 99.0 degrees and 101.0 degrees
Criticality Code Justification:
Feat
Special Features:
Weapon system essential
Material:
Steel comp 8740
Material Specification:
Aisi assn standard single material response
Surface Treatment:
Cadmium and chromate
Surface Treatment Specification:
Qq-p-416, type 2, class 2 federal specification single treatment response

NSN 5320-01-102-0369 Pin-rivet - Page 2 of 2



inread Series Designato
Unjf
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A528u0