## NSN 5320-01-102-1911

Pin-rivet - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5320-01-102-1911



### **Thread Class:**

3a

**Thread Direction:** 

**Right-hand** 

## Fastener Length:

Between 1.240 inches and 1.260 inches

### Head Style:

Err-090

#### Head Height:

Between 0.037 inches and 0.047 inches

### Width Between Flats:

Between 0.0791 inches and 0.0801 inches

#### Shank Diameter:

Between 0.1630 inches and 0.1635 inches

#### Shank Style:

Pin-rivet, straight, threaded

#### Head Major Diameter:

Between 0.242 inches and 0.262 inches

## Lubrication:

Cetyl alcohol, specification 305, hi-shear corp

#### Grip Length:

0.943 inches

### Thready Qty Per Inch (tpi):

32

## Thread Size:

0.164 inches

## Shear Strength:

125000 single pounds per square inch

### Material:

Steel comp xm-13

### Material Specification:

Ams 5629 assn standard single material response

#### Surface Treatment:

Passivate

## Surface Treatment Specification:

258, fscm 73197 mfr ref single treatment response

## **Thread Series Designator:**

Unjc

#### Shelf Life:

N/a

### Unit Of Measure:

---

# NSN 5320-01-102-1911

Pin-rivet - Page 2 of 2

Demilitarization:

No

Fiig:

A528u0

