NSN 5320-01-102-1913

Pin-rivet - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5320-01-102-1913



Thread Class:

3a

Thread Direction:

Right-hand

Fastener Length:

Between 2.161 inches and 2.201 inches

Head Style:

Err-090

Head Height:

Between 0.070 inches and 0.078 inches

Width Between Flats:

Between 0.1270 inches and 0.1295 inches

Shank Diameter:

Between 0.3110 inches and 0.3120 inches

Shank Style:

Pin-rivet, straight, threaded

Head Major Diameter:

Between 0.483 inches and 0.503 inches

Grip Length:

Between 1.689 inches and 1.750 inches

Thready Qty Per Inch (tpi):

24

Thread Size:

0.312 inches

Shear Strength:

156000 single pounds per square inch

Material:

Steel comp h11

Material Specification:

Ams 6485 assn standard single material response or ams 6487 assn standard single material response

Surface Treatment:

Nickel and cadmium

Surface Treatment Specification:

Ams 2416 assn standard single treatment response

Thread Series Designator:

Unjf

Specification Data:

80205-nas4450 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

NSN 5320-01-102-1913

Pin-rivet - Page 2 of 2

Demilitarization:

No

Fiig:

A528u0

