## NSN 5320-01-102-2758

Blind Rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-102-2758

Thread Class:
3a
Thread Direction:
Right-hand
Fastener Length:
Between 1.181 inches and 1.201 inches
Head Style:
Flush (flat) countersunk (included angle - less than 135 degrees w or w/o chamfer)
Shank Diameter:
Between 0.254 inches and 0.257 inches
Shank Style:
Blind rivet, nut and bolt (assembly)
Head Major Diameter:
0.3304 inches
Expansion Device:
Threaded mandrel
Grip Length:
0.875 inches
Thready Qty Per Inch (tpi):
32
Thread Size:
0.164 inches
Shear Strength:
125000 single pounds per square inch
Countersink Angle:
100.0 degrees
Special Features:
Cetyl alcohol lubrication on expander oily
Material:
Steel comp 305 sleeve or steel comp 302 sleeve
Surface Treatment:
Passivate sleeve
Surface Treatment Specification:
Qq-p-416, type 1, class 2 federal specification single treatment response expander
Thread Series Designator:
Unjc
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:

No

## NSN 5320-01-102-2758

Blind Rivet - Page 2 of 2



Fiig:

A040a0