# NSN 5320-01-102-8502

Pin-rivet - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5320-01-102-8502



#### **Thread Class:**

3a

**Thread Direction:** 

**Right-hand** 

## Fastener Length:

Between 1.224 inches and 1.249 inches

## Head Style:

Flush countersunk

#### Shank Diameter:

0.369 inches

#### Shank Style:

Pin-rivet, tapered, threaded

#### Head Major Diameter:

0.698 inches

## Tip Diameter:

0.3581 inches

### Lubrication:

Cetyl alcohol and dry film

#### Grip Length:

Between 0.740 inches and 0.755 inches

# Thready Qty Per Inch (tpi):

24

#### Min. Tensile Strength (psi):

160000 pounds per square inch

#### **Thread Size:**

0.312 inches

#### Shear Strength:

95000 single pounds per square inch

#### **Countersink Angle:**

Between 99.0 degrees and 101.0 degrees

#### Material:

Titanium alloy uns r56400

#### **Material Specification:**

Ams 4928 assn standard single material response

#### **Thread Series Designator:**

Unjf

# Shelf Life:

N/a

## Unit Of Measure:

--

## Demilitarization:

No

# NSN 5320-01-102-8502

Pin-rivet - Page 2 of 2

**Fiig:** A528u0

