## NSN 5320-01-106-1183

Pin-rivet - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5320-01-106-1183 **Head Style:** Err-090 **Head Height:** Between 0.128 inches and 0.147 inches Shank Diameter: Between 0.2480 inches and 0.2495 inches **Shank Style:** Pin-rivet, multiple grooved **Head Major Diameter:** Between 0.390 inches and 0.430 inches Lubrication: Cetyl alcohol **Grip Length:** Between 0.220 inches and 0.281 inches **Features Provided:** Casehardened and sealant vent groove Min. Tensile Strength (psi): 160000 pounds per square inch Hardness Rating: 77.0 rockwell superficial 15-n and 82.0 rockwell superficial 15-n **Shear Strength:** 95000 single pounds per square inch Material: Steel comp 8740 or steel comp 4340 or steel comp 4140 **Material Specification:** Astm a547 assn standard all material responses **Surface Treatment:** Cadmium and chromate **Surface Treatment Specification:** Qq-p-416, type 2, class 2 federal specification single treatment response **Specification Data:** 80205-nas1468 professional/industrial association standard Shelf Life: N/a **Unit Of Measure: Demilitarization:** 

No

Fiig:

A528u0