NSN 5320-01-106-3927



Pin-rivet - Page 1 of 1 View Online at https://aerobasegroup.com/nsn/5320-01-106-3927 Fastener Length: 0.639 inches **Head Style:** Flush countersunk **Shank Diameter:** Between 0.1880 inches and 0.1895 inches **Shank Style:** Stump **Head Major Diameter:** 0.305 inches Lubrication: Cetyl alcohol **Grip Length:** Between 0.313 inches and 0.375 inches **Features Provided:** Casehardened and sealant vent groove Min. Tensile Strength (psi): 160000 pounds per square inch **Hardness Rating:** 77.0 rockwell superficial 15-n and 82.0 rockwell superficial 15-n **Shear Strength:** 95000 single pounds per square inch **Countersink Angle:** Between 99.0 degrees and 101.0 degrees Material: Steel comp 8740 or steel comp 4340 or steel comp 4140 **Material Specification:** Astm a547 assn standard all material responses **Surface Treatment:** Cadmium and chromate **Surface Treatment Specification:** Qq-p-416, type 2, class 2 federal specification single treatment response **Specification Data:** 80205-nas1416 professional/industrial association standard Shelf Life: N/a **Unit Of Measure: Demilitarization:**

No Fiig:

A528u0