

NSN 5320-01-107-6112 Pin-rivet - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5320-01-107-6112 **Thread Class:** За **Thread Direction:** Right-hand Fastener Length: 0.763 inches **Head Style:**

Err-090 **Head Height:**

Between 0.064 inches and 0.074 inches

Hole Diameter:

Between 0.104 inches and 0.119 inches

Shank Diameter:

Between 0.2016 inches and 0.2026 inches

Shank Style:

Err-090

Head Major Diameter:

Between 0.357 inches and 0.377 inches

Hole Depth:

Between 0.115 inches and 0.135 inches

Lubrication:

Cetyl alcohol, specification 305, hi-shear corp

Grip Length:

0.438 inches

Min. Tensile Strength (psi):

125000 pounds per square inch

Minimum Yield Strength:

4350 pounds per square inch

Thread Size:

0.190 inches

Shear Strength:

8100 double pounds per square inch

Criticality Code Justification:

Aaze

Material:

Steel comp 431

Material Specification:

Qq-s-763 federal specification single material response

Surface Treatment:

Cadmium

Surface Treatment Specification:

Qq-p-416, type 11, class 3 federal specification single treatment response

NSN 5320-01-107-6112

Pin-rivet - Page 2 of 2



Thread Series Designator:
Unjf
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A528u0