NSN 5320-01-108-1160

Solid Rivet - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5320-01-108-1160

Fastener Length:
Between 2.990 inches and 3.010 inches
Head Style:
Undersized oval countersunk
Head Height:
Between 0.004 inches and 0.006 inches
Shank Diameter:
Between 0.249 inches and 0.252 inches
Shank Style:
Straight w/radius chamfered tip
Head Major Diameter:
Between 0.3710 inches and 0.3948 inches
Head Minor Diameter:
0.316 mils and 0.326 centimeters
Countersink Height:
0.060 inches
Shear Strength:
33000 single pounds per square inch
Countersink Angle:
Between 99.5 degrees and 100.5 degrees
Heat Treatment:
T-4 solution heat treated
Material:
Aluminum alloy 2017
Material Specification:
Qq-a-430 federal specification single material response
Surface Treatment:
Anodize
Surface Treatment Specification:
Mil-a-8625 military specification single treatment response or mil-c-5541 military specification single treatment response
Specification Data:
80205-nas1097 professional/industrial association standard
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A040a0
Mil-std (military Standard):
Mil-a-8625 spec.