NSN 5320-01-109-6086

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-109-6086 **Thread Direction:** Right-hand Fastener Length: 18.35 millimeters **Head Style:** Err-090 **Head Height:** Between 1.40 millimeters and 1.60 millimeters Width Between Flats: Between 1.61 millimeters and 1.64 millimeters **Shank Diameter:** Between 3.978 millimeters and 3.990 millimeters **Shank Style:** Pin-rivet, straight, threaded **Head Major Diameter:** Between 7.75 millimeters and 8.15 millimeters Lubrication: Cetyl alcohol, specification 305, hi-shear corp **Grip Length:** 10.00 millimeters **Thread Size:** 4.00 millimeters **Thread Pitch In Millimeters:** 0.70 **Shear Strength:** 16400 double newtons per square millimeter **Thread Tolerance Class:** 4h internal Material: Iron alloy 660 **Material Specification:** Ams 5737 assn standard single material response or ams 5731 assn standard single material response **Surface Treatment: Passivate Thread Series Designator:** Iso m Shelf Life: N/a **Unit Of Measure:**

Demilitarization:

No

NSN 5320-01-109-6086

Pin-rivet - Page 2 of 2



Fiig:

A528u0