

View Online at <https://aerobasegroup.com/nsn/5320-01-110-8861>

**Fastener Length:**

0.323 inches

**Head Style:**

Flush (flat) countersunk (included angle - less than 135 degrees w or w/o chamfer)

**Shank Diameter:**

Between 0.139 inches and 0.143 inches

**Shank Style:**

Self-plugging

**Head Major Diameter:**

Between 0.221 inches and 0.229 inches

**Expansion Device:**

Serrated stem-type w

**Grip Length:**

Between 0.126 inches and 0.187 inches

**Min. Tensile Strength (psi):**

345 pounds per square inch

**Shear Strength:**

560 single pounds per square inch

**Countersink Angle:**

Between 98.0 degrees and 101.0 degrees

**Material:**

Aluminum alloy 5056 sleeve

**Material Specification:**

Qq-a-430 federal specification single material response sleeve

**Surface Treatment:**

Anodize expander

**Surface Treatment Specification:**

Mil-a-8625 military specification 1st treatment response expander or mil-c-5541 military specification 2nd treatment response expander

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A040a0

**Mil-std (military Standard):**

Mil-a-8625 spec.