
# NSN 5320-01-112-1587

Pin-rivet - Page 1 of 1



## Fastener Length:

0.573 inches

# Head Style:

Err-090

# Head Height:

Between 0.078 inches and 0.088 inches

# Shank Diameter:

Between 0.1880 inches and 0.1895 inches

#### Shank Style:

Stump

#### Head Major Diameter:

Between 0.302 inches and 0.317 inches

#### Lubrication:

Cetyl alcohol

# Grip Length:

Between 0.220 inches and 0.281 inches

# Features Provided:

Casehardened and sealant vent groove

# Min. Tensile Strength (psi):

160000 pounds per square inch

# Hardness Rating:

77.0 rockwell superficial 15-n and 82.0 rockwell superficial 15-n

#### Shear Strength:

95000 single pounds per square inch

Material:

Steel comp 8740 or steel comp 4340 or steel comp 4140

# Material Specification:

Astm a547 assn standard all material responses

#### Surface Treatment:

Cadmium and chromate

#### Surface Treatment Specification:

Qq-p-416, type 2, class 2 federal specification single treatment response

#### **Specification Data:**

80205-nas1496 professional/industrial association standard

#### Shelf Life:

N/a

# Unit Of Measure:

---

### Demilitarization:

No

Fiig:

A528u0

