## NSN 5320-01-116-6668



Pin-rivet - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5320-01-116-6668 **Thread Class:** За **Thread Direction:** Right-hand Fastener Length: Between 0.973 inches and 1.013 inches **Head Style:** Flush countersunk Width Between Flats: Between 0.0947 inches and 0.0967 inches **Shank Diameter:** Between 0.2485 inches and 0.2495 inches **Shank Style:** Pin-rivet, straight, threaded **Head Major Diameter:** 0.399 inches **Grip Length:** Between 0.563 inches and 0.625 inches Thready Qty Per Inch (tpi): 28 **Thread Size:** 0.250 inches **Shear Strength:** 156000 single pounds per square inch **Countersink Angle:** Between 99.0 degrees and 101.0 degrees Material: Steel comp h11 **Material Specification:** Ams 6485 assn standard single material response or ams 6487 assn standard single material response **Surface Treatment:** Nickel and cadmium **Surface Treatment Specification:** Ams 2416 assn standard single treatment response **Thread Series Designator:** Unjf

**Specification Data:** 

80205-nas4452 professional/industrial association standard

Shelf Life:

N/a

**Unit Of Measure:** 

--

## NSN 5320-01-116-6668

Pin-rivet - Page 2 of 2



Demilitarization:

No

Fiig:

A528u0