## NSN 5320-01-117-3507

Blind Rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-117-3507

## Thread Class:

3a

## **Thread Direction:**

Left-hand

## Head Style:

Flush (flat) countersunk (included angle - less than 135 degrees w or w/o chamfer)

#### Shank Diameter:

0.2209 inches

#### Shank Style:

Threaded self-plugging shank w/sleeve

## Head Major Diameter:

0.337 inches

## **Expansion Device:**

Threaded stem

## Lubrication:

Cetyl alcohol

## Grip Length:

Between 0.814 inches and 0.875 inches

## Thready Qty Per Inch (tpi):

40

## Hardness Rating:

43.5 rockwell c nut and 46.5 rockwell c nut

## Thread Size:

0.138 inches

## **Countersink Angle:**

Between 99.0 degrees and 101.0 degrees

## **Special Features:**

0.2055 in. Second shank diameter

## Material:

Steel comp 8740 nut

## **Material Specification:**

Mil-s-6049 military specification single material response nut

## Surface Treatment:

Cadmium sleeve and chromate sleeve

## Surface Treatment Specification:

Qq-p-416, type 2, class 3 federal specification single treatment response sleeve

## **Thread Series Designator:**

Unf

## Shelf Life:

N/a

## Unit Of Measure:

--

# NSN 5320-01-117-3507

Blind Rivet - Page 2 of 2

Demilitarization:

No

Fiig:

A040a0

Mil-std (military Standard):

Mil-s-6049 spec.

