## NSN 5320-01-121-2791

Pin-rivet - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5320-01-121-2791



## **Thread Class:** 3a **Thread Direction: Right-hand** Fastener Length: Between 1.690 inches and 1.710 inches Head Style: Flush countersunk Width Between Flats: Between 0.0791 inches and 0.0806 inches Shank Diameter: Between 0.1890 inches and 0.1895 inches Shank Style: Pin-rivet, straight, threaded Head Major Diameter: 0.3813 inches Lubrication: Cetyl alcohol, specification 305, hi-shear corp **End Application:** W/s: aircraft, b-1b; aircraft, eagle f-15 Grip Length: 1.380 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 160000 pounds per square inch **Thread Size:** 0.190 inches **Countersink Angle:** 100.0 degrees Material: Titanium alloy uns r56400 **Material Specification:** Ams 4928 assn standard single material response or ams 4967 assn standard single material response **Thread Series Designator:** Unjf Shelf Life: N/a Unit Of Measure:

## **Demilitarization:**

No

---

## NSN 5320-01-121-2791

Pin-rivet - Page 2 of 2

**Fiig:** A528u0

