## NSN 5320-01-123-6464



Pin-rivet - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5320-01-123-6464 **Thread Class:** За **Thread Direction:** Right-hand Fastener Length: Between 0.598 inches and 0.638 inches **Head Style:** Err-090 **Head Height:** Between 0.061 inches and 0.069 inches Width Between Flats: Between 0.0947 inches and 0.0967 inches **Shank Diameter:** Between 0.2485 inches and 0.2495 inches **Shank Style:** Pin-rivet, straight, threaded **Head Major Diameter:** Between 0.398 inches and 0.413 inches Lubrication: Dry film **Grip Length:** Between 0.189 inches and 0.250 inches Thready Qty Per Inch (tpi): 28 **Thread Size:** 0.250 inches **Shear Strength:** 156000 single pounds per square inch Material: Steel comp h11 **Material Specification:** Ams 6485 assn standard single material response or ams 6487 assn standard single material response **Surface Treatment:** Nickel and cadmium **Surface Treatment Specification:** Ams 2416 assn standard single treatment response **Thread Series Designator:** Unjf

**Specification Data:** 

80205-nas4450 professional/industrial association standard

Shelf Life:

N/a

## NSN 5320-01-123-6464

Pin-rivet - Page 2 of 2



| ш | ın | 10 | <i>(</i> )+ | Measure: |  |
|---|----|----|-------------|----------|--|
|   |    |    |             |          |  |

--

Demilitarization:

No

Fiig:

A528u0